

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** Thinner for Oxyd-Stop-PM
- **Article number:** 520 0067 0
- **Application of the substance / the preparation** Thinner
- **Manufacturer/Supplier:**
bredent GmbH & Co.KG
Weißenhörner Straße 2
89250 Senden
Tel: +49 (0) 7309/872-0
Fax: +49 (0) 7309/872-24
- **Further information obtainable from:**
R & D
e-mail: R.D@bredent.com
- **Information in case of emergency:** Tel.: +49 (0) 6132-84436 (24 h)

2 Hazards identification

- **Hazard description:**



Xn Harmful
F Highly flammable

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 15 Contact with water liberates extremely flammable gases.
R 20/21 Harmful by inhalation and in contact with skin.
R 38 Irritating to skin.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization:**
- **CAS No. Description**
- **Identification number(s)**
- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1330-20-7	xylene	Xn, Xi; R 10-20/21-38	50-100%
EINECS: 215-535-7			

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 2)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

Trade name: Thinner for Oxyd-Stop-PM

(Contd. of page 1)

- In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

OES	Short-term value: 662 mg/m ³ , 150 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

(Contd. on page 3)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

Trade name: Thinner for Oxyd-Stop-PM

(Contd. of page 2)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range:	-34°C
Boiling point/Boiling range:	137°C

· **Flash point:** 23°C

· **Ignition temperature:** 500°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	7 Vol %

· **Vapour pressure at 20°C:** 6.7-8.2 hPa

· **Density at 20°C:** 0.87 g/cm³

· **Solubility in / Miscibility with water at 20°C:** 0.2 g/l

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

Trade name: *Thinner for Oxyd-Stop-PM*

(Contd. of page 3)

Organic solvents:	97.2 %
--------------------------	--------

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** Contact with water releases flammable gases.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

12 Ecological information

- **General notes:**

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.

- **Danger code (Kemler):** 30

- **UN-Number:** 1307

- **Packaging group:** III

- **Hazard label:** 3

(Contd. on page 5)

GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

Trade name: *Thinner for Oxyd-Stop-PM*

(Contd. of page 4)

· **Description of goods:** 1307 XYLENES, mixture· **Maritime transport IMDG:**

- **IMDG Class:** 3
- **UN Number:** 1307
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No
- **Proper shipping name:** XYLENES, mixture

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1307
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** XYLENES, mixture

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xn Harmful
F Highly flammable

· **Hazard-determining components of labelling:**

xylene

· **Risk phrases:**

10 Flammable.
15 Contact with water liberates extremely flammable gases.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.

· **Safety phrases:**

7/8 Keep container tightly closed and dry.
36/37 Wear suitable protective clothing and gloves.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
60 This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.
20/21 Harmful by inhalation and in contact with skin.

(Contd. on page 6)

GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 04.11.2004

Trade name: Thinner for Oxyd-Stop-PM

(Contd. of page 5)

38 Irritating to skin.

- **Department issuing MSDS:** R & D
- **Contact:** R & D

GB