

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

## 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** *Die varnish, light-curing, opaque*
- **Article number:** 540 0010 1, 540 0010 3, 540 0010 4
- **Application of the substance / the preparation** *Light-curing die varnish.*
- **Manufacturer/Supplier:**  
*breident GmbH & Co.KG  
 Weißenhorner Straße 2  
 89250 Senden  
 Tel: +49 (0) 7309/872-0  
 Fax: +49 (0) 7309/872-24*
- **Further information obtainable from:**  
*R & D  
 e-mail: R.D@breident.com*
- **Information in case of emergency:** *Tel.: +49 (0) 6132-84436 (24 h)*

## 2 Hazards identification

- **Hazard description:**



*Xi Irritant  
 F Highly flammable*

- **Information concerning particular hazards for human and environment:**

*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*

*R 11 Highly flammable.*

*R 37/38 Irritating to respiratory system and skin.*

*R 43 May cause sensitisation by skin contact.*

*R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

- **Classification system:**

*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*

## 3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** *Mixture of substances listed below with nonhazardous additions.*

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Xi,  F; R 11-37/38-43	10-25%
	polymere based on polyetherpolyole, acrylic ester, modified N; R 51/53	10-25%
CAS: 75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)-phosphineoxide Xn; R 62-52/53	1-5%

- **Additional information:** *For the wording of the listed risk phrases refer to section 16.*

## 4 First aid measures

- **After inhalation:**

*Supply fresh air and to be sure call for a doctor.*

*In case of unconsciousness place patient stably in side position for transportation.*

- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

(Contd. on page 2)

GB

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

**Trade name: Die varnish, light-curing, opaque**

(Contd. of page 1)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

## 5 Fire-fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

**80-62-6 methyl methacrylate**

OES	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 208 mg/m <sup>3</sup> , 50 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Avoid contact with the eyes and skin.  
Immediately remove all soiled and contaminated clothing  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.

(Contd. on page 3)

GB

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

Trade name: Die varnish, light-curing, opaque

(Contd. of page 2)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Fluid
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 101°C

· **Flash point:** 10°C

· **Ignition temperature:** 415°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

**Lower:** 2.1 Vol %

**Upper:** 12.5 Vol %

· **Vapour pressure at 20°C:** 47 hPa

· **Density:** Not determined.

· **Solubility in / Miscibility with**

**water:** Not miscible or difficult to mix.

(Contd. on page 4)

GB

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

**Trade name: Die varnish, light-curing, opaque**

(Contd. of page 3)

- **Solvent content:**
- **Organic solvents:** 0.0 %

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

*polymere based on polyetherpolyole, acrylic ester, modified*

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

*75980-60-8 diphenyl(2,4,6,-trimethylbenzoyl)-phosphineoxide*

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

*The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:*

*Irritant*

- **Sensitisation** May cause sensitisation by skin contact.

## 12 Ecological information

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **General notes:**

*Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water*

*Do not allow product to reach ground water, water course or sewage system.*

*Danger to drinking water if even small quantities leak into the ground.*

*Harmful to aquatic organisms*

## 13 Disposal considerations

- **Product:**

- **Recommendation**

*Must not be disposed together with household garbage. Do not allow product to reach sewage system.*

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

Trade name: Die varnish, light-curing, opaque

(Contd. of page 4)

## 14 Transport information

### · Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1993
- **Packaging group:** II
- **Hazard label:** 3
- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), special provision 640D

### · Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** Yes
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, Polyetherpolyole, Acrylic acid ester, modified)

### · Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label:** 3
- **Packaging group:** II
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)

## 15 Regulatory information

### · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

### · Code letter and hazard designation of product:

Xi Irritant  
F Highly flammable

### · Hazard-determining components of labelling:

methyl methacrylate

### · Risk phrases:

11 Highly flammable.  
37/38 Irritating to respiratory system and skin.  
43 May cause sensitisation by skin contact.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 6)

GB

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 20.01.2005

**Trade name: Die varnish, light-curing, opaque**

(Contd. of page 5)

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe fumes/aerosol.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 28 After contact with skin, wash immediately with plenty of soap and water.
- 33 Take precautionary measures against static discharges.
- 37 Wear suitable gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 60 This material and its container must be disposed of as hazardous waste.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant R-phrases**

- 11 Highly flammable.
- 37/38 Irritating to respiratory system and skin.
- 43 May cause sensitisation by skin contact.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 62 Possible risk of impaired fertility.

· **Department issuing MSDS: R & D**

· **Contact: R & D**

GB