

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** *Retension adhesive, white - Thinner*
- **Article number:** 540 0071 2
- **Application of the substance / the preparation** *Thinner.*
- **Manufacturer/Supplier:**
*bredent GmbH & Co.KG
 Weißenhorner Straße 2
 89250 Senden
 Tel: +49 (0) 7309/872-0
 Fax: +49 (0) 7309/872-24*
- **Further information obtainable from:**
*R & D
 e-mail: R.D@bredent.com*
- **Information in case of emergency:** *Tel.: +49 (0) 6132-84436 (24 h)*

2 Hazards identification

- **Hazard description:**



*Xi Irritant
 F Highly flammable*

- **Information concerning particular hazards for human and environment:**
*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
 Has a narcotizing effect.
 R 11 Highly flammable.
 R 36 Irritating to eyes.
 R 66 Repeated exposure may cause skin dryness or cracking.
 R 67 Vapours may cause drowsiness and dizziness.*

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone	Xi, F; R 11-36-66-67	50-100%
CAS: 84929-31-7 EINECS: 284-515-8	ethereal oil	Xn, F; R 11-65	1-5%

4 First aid measures

- **General information:**
*Take affected persons out into the fresh air.
 Immediately remove any clothing soiled by the product.*
- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:**
*Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.*
- **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*

(Contd. on page 2)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

Trade name: Retension adhesive, white - Thinner

(Contd. of page 1)

· **After swallowing:** Call a doctor immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the substance, its products of combustion or resulting gases:**
In case of fire, the following can be released:
Carbon monoxide (CO)
Can form explosive gas-air mixtures.
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Person-related safety precautions:**
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Dispose contaminated material as waste according to item 13.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 3)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

Trade name: Retension adhesive, white - Thinner

(Contd. of page 2)

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

OES	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm
	New, IOELV

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Filter AX

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

Preventive skin protection by use of skin-protecting agents is recommended.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	Red
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55.8-56.6°C

· **Flash point:** -18°C

· **Ignition temperature:** 540°C

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 2.2 Vol %

Upper: 12.8 Vol %

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

Trade name: Retension adhesive, white - Thinner

(Contd. of page 3)

- | | |
|--|------------------------|
| · Vapour pressure at 20°C: | 233 hPa |
| · Density at 20°C: | 0.79 g/cm ³ |
| · Solubility in / Miscibility with water: | Partly miscible. |
| · Solvent content: | |
| Organic solvents: | 75.0 % |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions**
Reacts with oxidizing agents.
Photoreactive.
Possible formation of peroxide.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation** Must be specially treated adhering to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

Trade name: Retension adhesive, white - Thinner

(Contd. of page 4)

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1993
- **Packaging group:** II
- **Hazard label:** 3
- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), special provision 640D

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label:** 3
- **Packaging group:** II
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xi Irritant
F Highly flammable

· Risk phrases:

11 Highly flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.

(Contd. on page 6)

GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 21.08.2007

Revision: 01.12.2005

Trade name: Retension adhesive, white - Thinner

23 Do not breathe fumes/aerosol.

(Contd. of page 5)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

11 Highly flammable.

36 Irritating to eyes.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: R & D**· Contact: R & D**

GB