

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** Gloss and hardening agent for plasters
- **Article number:** 550 0000 1, 550 0000 2
- **Application of the substance / the preparation** Liquid for coating and hardening gypsum surfaces.
- **Manufacturer/Supplier:**
bredent GmbH & Co.KG
Weißenhörner Straße 2
89250 Senden
Tel: +49 (0) 7309/872-0
Fax: +49 (0) 7309/872-24
- **Further information obtainable from:**
R & D
e-mail: R.D@bredent.com
- **Information in case of emergency:** (001)3523233500 (24 h)

2 Hazards identification

- **Hazard description:**



Xi Irritant
F Highly flammable

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Has a narcotizing effect.
R 11 Highly flammable.
R 36 Irritating to eyes.
R 67 Vapours may cause drowsiness and dizziness.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone	Xi, F; R 11-36-66-67	50-100%
CAS: 64-17-5 EINECS: 200-578-6	ethanol	F; R 11	1-5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

Trade name: Gloss and hardening agent for plasters

(Contd. of page 1)

- **After swallowing:** *If symptoms persist consult doctor.*

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** *No special measures required.*

6 Accidental release measures

- **Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.*
- **Measures for environmental protection:** *Do not allow to enter sewers/ surface or ground water.*
- **Measures for cleaning/collecting:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.*

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
*Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).*
- **Information about fire - and explosion protection:**
*Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.*
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Store in cool, dry conditions in well sealed receptacles.*

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** *No further data; see item 7.*

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

OES	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm
	New, IOELV

64-17-5 ethanol

OES	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

- **Additional information:** *The lists valid during the making were used as basis.*

- **Personal protective equipment:**
- **General protective and hygienic measures:**
*The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.*
- **Respiratory protection:** *Use suitable respiratory protective device in case of insufficient ventilation.*

(Contd. on page 3)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

Trade name: **Gloss and hardening agent for plasters**

(Contd. of page 2)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55°C

· **Flash point:** -19°C· **Ignition temperature:** 180°C· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

Lower:	2.6 Vol %
Upper:	13.0 Vol %

· **Vapour pressure at 20°C:** 233 hPa· **Density at 20°C:** 0.85 g/cm³· **Solubility in / Miscibility with water:** Fully miscible.· **Solvent content:**

Organic solvents:	>90.0 %
--------------------------	---------

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

Trade name: Gloss and hardening agent for plasters

(Contd. of page 3)

· **Solids content:** <10.0 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 3 Flammable liquids.

· **Danger code (Kemler):** 33

· **UN-Number:** 1993

· **Packaging group:** II

(Contd. on page 5)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

Trade name: Gloss and hardening agent for plasters

(Contd. of page 4)

- **Hazard label:** 3
- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), special provision 640D

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xi Irritant
F Highly flammable
- **Hazard-determining components of labelling:**
acetone
cellulose nitrate
ethanol
- **Risk phrases:**
11 Highly flammable.
36 Irritating to eyes.
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
7/9 Keep container tightly closed and in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
60 This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 6)

GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 11.02.2008

Revision: 03.02.2005

Trade name: Gloss and hardening agent for plasters

(Contd. of page 5)

· **Relevant R-phrases**

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS: R & D**

· **Contact: R & D**

GB